



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm					
NAME: UFO		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:		Shielding Angle:	

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 166.17 lm/W
MODEL	UFO	Imax(cd/klm)	807.7	S/MH(C0/180)	0.95	
NOMINAL POWER(W)	200	LOR(%)	100.0	S/MH(C90/270)	0.92	
RATED VOLTAGE(V)	220.0	TOTAL FLUX(lm/klm)	1000.00	η UP,DN(C0-180)	0.3,48.6	
NOMINAL FLUX(lm)	33331.8	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.3,50.8	
LAMPS INSIDE	1	η up(%)	0.6	CIBSE SHR NOM	0.75	
TEST VOLTAGE(V)	220.0	η down(%)	99.4	CIBSE SHR MAX	0.95	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

C0 PLANE ISOLUX DIAGRAM (UNIT:lx/klm)


C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	761.3	764.1	761.8	768.5	785.0	785.4	784.0	774.2	0- 10	75.74	75.74	7.57,7.57
20	584.0	597.6	596.5	610.3	645.9	643.6	631.3	609.1	10- 20	197.2	272.9	27.3,27.3
30	373.4	396.2	402.6	417.9	453.2	441.5	417.6	397.8	20- 30	235.3	508.3	50.8,50.8
40	209.8	219.7	226.1	242.9	267.0	247.9	226.5	221.2	30- 40	196.5	704.8	70.5,70.5
50	116.9	121.0	124.6	137.1	151.4	136.3	120.9	120.7	40- 50	135.1	839.9	84,84
60	59.14	62.54	64.92	72.62	81.24	71.08	61.45	61.63	50- 60	84.95	924.8	92.5,92.5
70	25.35	27.96	29.26	33.02	37.14	31.71	27.27	26.78	60- 70	46.08	970.9	97.1,97.1
80	7.137	8.752	9.146	10.66	12.41	9.975	8.137	7.893	70- 80	19.49	990.4	99,99
90	0.1075	0.2495	0.2110	0.4742	0.6641	0.3969	0.1073	0.1268	80- 90	4.061	994.5	99.4,99.4
100	0.1961	0.1736	0.1559	0.2015	0.2572	0.1557	0.1243	0.1367	90-100	0.2179	994.7	99.5,99.5
110	0.3628	0.3233	0.2902	0.2804	0.2165	0.2294	0.2456	0.2695	100-110	0.2220	994.9	99.5,99.5
120	0.6308	0.5747	0.5212	0.4993	0.4010	0.4230	0.4496	0.4911	110-120	0.3743	995.3	99.5,99.5
130	1.047	0.9840	0.9067	0.8574	0.7053	0.7426	0.7841	0.8486	120-130	0.5935	995.9	99.6,99.6
140	1.612	1.559	1.470	1.386	1.174	1.226	1.278	1.369	130-140	0.8532	996.7	99.7,99.7
150	2.249	2.210	2.127	2.030	1.781	1.832	1.890	2.004	140-150	1.057	997.8	99.8,99.8
160	2.860	2.830	2.758	2.673	2.442	2.479	2.544	2.662	150-160	1.073	998.9	99.9,99.9
170	3.363	3.322	3.271	3.233	3.090	3.098	3.141	3.245	160-170	0.8285	999.7	100,100
180	3.485	3.480	3.482	3.518	3.494	3.481	3.476	3.517	170-180	0.3195	1000.0	100,100
DEG	LUMINOUS INTENSITY:cd/klm									UNIT: lm/klm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	6155	9872
80	11323	14276
75	15505	18697
70	20422	23191
65	25934	28630
60	32586	35197
55	40654	43045
50	50097	52542
45	61330	64399


C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 02
Test Date: 2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity: 65.0%
Test Distance: 8.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.99
1.0	1.08	1.05	1.02	1.06	1.03	1.01	1.02	.99	.97	.98	.96	.94	.94	.93	.91	.89
2.0	.98	.93	.89	.96	.92	.88	.93	.89	.86	.90	.86	.84	.87	.84	.82	.80
3.0	.89	.83	.78	.88	.82	.77	.85	.80	.76	.82	.78	.75	.80	.76	.74	.72
4.0	.82	.75	.70	.80	.74	.69	.78	.73	.68	.76	.71	.67	.74	.70	.66	.65
5.0	.75	.68	.63	.74	.67	.62	.72	.66	.62	.70	.65	.61	.68	.64	.60	.59
6.0	.69	.62	.57	.68	.62	.57	.67	.61	.56	.65	.60	.56	.64	.59	.55	.54
7.0	.64	.57	.52	.64	.57	.52	.62	.56	.52	.61	.55	.51	.59	.55	.51	.49
8.0	.60	.53	.48	.59	.52	.48	.58	.52	.47	.57	.51	.47	.56	.51	.47	.45
9.0	.56	.49	.44	.55	.49	.44	.54	.48	.44	.53	.48	.44	.52	.47	.44	.42
10.0	.52	.46	.41	.52	.45	.41	.51	.45	.41	.50	.45	.41	.49	.44	.41	.39



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 02
Test Date: 2019-08-21

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity: 65.0%
Test Distance: 8.000m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm					
NAME: UFO		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:		Shielding Angle:	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.225	.128	.041	.218	.124	.040	.205	.118	.038	.193	.111	.036	.182	.105	.034		
2.0	.217	.119	.036	.211	.116	.036	.199	.111	.034	.189	.106	.033	.179	.101	.032		
3.0	.205	.109	.033	.200	.107	.032	.190	.103	.031	.181	.099	.030	.172	.095	.030		
4.0	.193	.100	.030	.189	.099	.029	.180	.096	.029	.172	.092	.028	.165	.089	.027		
5.0	.182	.093	.027	.178	.091	.027	.170	.089	.026	.163	.086	.026	.157	.084	.025		
6.0	.172	.086	.025	.168	.085	.024	.161	.083	.024	.155	.081	.024	.149	.079	.023		
7.0	.162	.080	.023	.159	.079	.023	.153	.077	.022	.147	.076	.022	.142	.074	.022		
8.0	.154	.075	.021	.151	.074	.021	.145	.073	.021	.140	.071	.020	.136	.070	.020		
9.0	.146	.070	.020	.143	.070	.020	.138	.068	.019	.134	.067	.019	.129	.066	.019		
10.0	.138	.066	.018	.136	.066	.018	.132	.065	.018	.128	.063	.018	.124	.062	.018		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.195	.195	.195	.166	.166	.166	.114	.114	.114	.065	.065	.065	.021	.021	.021	
1.0	.179	.161	.145	.153	.138	.125	.105	.095	.086	.060	.055	.050	.019	.018	.016	
2.0	.167	.137	.111	.143	.118	.096	.098	.081	.067	.056	.047	.039	.018	.015	.013	
3.0	.156	.118	.088	.134	.102	.076	.092	.071	.053	.053	.041	.031	.017	.013	.010	
4.0	.147	.104	.071	.126	.090	.062	.087	.063	.043	.050	.037	.026	.016	.012	.008	
5.0	.140	.093	.059	.120	.080	.051	.083	.056	.036	.048	.033	.021	.015	.011	.007	
6.0	.132	.084	.050	.114	.073	.043	.079	.051	.031	.046	.030	.018	.015	.010	.006	
7.0	.126	.077	.043	.108	.067	.037	.075	.047	.026	.043	.028	.016	.014	.009	.005	
8.0	.120	.071	.037	.103	.062	.032	.072	.043	.023	.042	.025	.014	.013	.008	.005	
9.0	.115	.066	.033	.099	.057	.029	.068	.040	.020	.040	.024	.012	.013	.008	.004	
10.0	.110	.062	.030	.095	.053	.026	.066	.038	.018	.038	.022	.011	.012	.007	.004	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm										
NAME: UFO					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	11.8	13.0	12.1	13.2	13.4	12.1	13.2	12.3	13.4	13.6
3H	12.3	13.3	12.5	13.6	13.8	12.6	13.7	12.8	13.9	14.1
4H	12.4	13.4	12.7	13.6	13.9	12.7	13.7	13.0	14.0	14.2
6H	12.4	13.4	12.7	13.6	13.9	12.8	13.7	13.1	14.0	14.3
8H	12.4	13.3	12.7	13.6	13.9	12.8	13.7	13.1	14.0	14.3
12H	12.4	13.2	12.7	13.5	13.8	12.8	13.7	13.1	13.9	14.2
4H 2H	12.0	13.1	12.3	13.3	13.5	12.2	13.3	12.5	13.5	13.8
3H	12.6	13.5	12.9	13.8	14.1	12.9	13.8	13.2	14.1	14.4
4H	12.8	13.6	13.2	13.9	14.2	13.1	13.9	13.5	14.2	14.6
6H	12.9	13.6	13.3	13.9	14.3	13.2	14.0	13.6	14.3	14.7
8H	12.9	13.5	13.3	13.9	14.3	13.3	13.9	13.7	14.3	14.7
12H	12.9	13.5	13.3	13.8	14.3	13.3	13.9	13.7	14.3	14.7
8H 4H	12.8	13.5	13.2	13.9	14.2	13.1	13.8	13.5	14.2	14.5
6H	13.0	13.5	13.4	13.9	14.4	13.3	13.9	13.8	14.3	14.7
8H	13.0	13.5	13.5	13.9	14.4	13.4	13.9	13.8	14.3	14.7
12H	13.0	13.4	13.5	13.9	14.3	13.4	13.8	13.9	14.3	14.8
12H 4H	12.8	13.4	13.2	13.8	14.2	13.1	13.7	13.5	14.1	14.5
6H	13.0	13.4	13.4	13.9	14.3	13.3	13.8	13.8	14.2	14.7
8H	13.0	13.4	13.5	13.9	14.4	13.4	13.8	13.9	14.2	14.7
Variations with the observer position at spacings:										
S = 1.0H	+ 0.7 / - 1.0					+ 0.7 / - 0.9				
1.5H	+ 0.7 / - 0.5					+ 0.6 / - 0.5				
2.0H	+ 1.4 / - 1.2					+ 1.4 / - 1.2				

CIE Pub.117, 33332 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 12.2$)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 02
Test Date: 2019-08-21

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity: 65.0%
Test Distance: 8.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	73	64	59	72	64	59	71	63	59	54
0.80	82	74	68	81	73	68	80	72	68	62
1.00	89	81	76	88	80	75	86	81	75	69
1.25	94	87	82	93	86	82	91	85	81	75
1.50	98	91	87	97	91	86	94	89	85	79
2.00	103	97	93	101	96	92	98	94	90	84
2.50	106	100	96	104	99	95	100	96	93	86
3.00	108	103	99	106	102	98	102	99	96	88
4.00	111	107	103	108	105	102	104	102	99	91
5.00	112	109	106	110	107	105	106	103	101	93
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 02
Test Date: 2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity: 65.0%
Test Distance: 8.000m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 02
Test Date: 2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity: 65.0%
Test Distance: 8.000m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	31010
L_0~180(75)av	19721
L_0~180(85)av	11067
L_90~270(65)av	27903
L_90~270(75)av	17965
L_90~270(85)av	8790
L_45(65)av	29512
L_45(75)av	18923
L_45(85)av	10054

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: 02
Test Date: 2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity: 65.0%
Test Distance: 8.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:221.61V I:0.9245A P:200.59W PF:0.9790 Freq:49.98Hz Lamp Flux:33331.8x1 lm		
NAME: UFO	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd/klm

C(DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	807	807	807	807	807	807	807	807	807	807	807	807						
5	801	802	801	800	800	802	805	805	806	807	806	803						
10	761	766	762	762	763	774	785	785	786	784	780	768						
15	688	698	695	694	695	714	731	731	731	726	720	700						
20	584	597	598	597	598	622	646	644	643	631	621	597						
25	480	497	502	502	502	529	550	546	540	525	516	494						
30	373	392	400	403	403	433	453	447	436	418	408	387						
35	280	294	301	305	307	337	354	344	329	311	305	292						
40	210	218	221	226	229	257	267	257	239	227	225	218						
45	157	162	164	168	172	194	201	192	176	166	166	162						
50	117	120	122	125	129	145	151	142	130	121	123	118						
55	84.6	86.9	89.6	91.1	95.0	107	112	104	95.3	87.2	89.8	85.3						
60	59.1	61.4	63.7	64.9	68.2	77.0	81.2	74.2	68.0	61.5	63.6	59.7						
65	39.8	41.8	43.8	44.6	47.0	53.3	56.5	50.9	46.4	42.0	43.2	40.2						
70	25.4	27.2	28.7	29.3	30.8	35.3	37.1	33.5	29.9	27.3	27.7	25.8						
75	14.6	16.2	17.4	17.9	18.6	21.9	22.9	20.5	18.0	16.3	16.5	14.9						
80	7.14	8.39	9.11	9.15	9.63	11.7	12.4	10.7	9.28	8.14	8.42	7.37						
85	1.95	2.73	3.24	3.17	3.54	4.42	5.14	3.80	3.26	2.46	2.62	2.12						
90	0.11	0.16	0.34	0.21	0.29	0.66	0.66	0.50	0.29	0.11	0.17	0.08						
95	0.14	0.13	0.12	0.12	0.20	0.39	0.40	0.33	0.19	0.09	0.09	0.10						
100	0.20	0.18	0.17	0.16	0.16	0.24	0.26	0.19	0.12	0.12	0.13	0.14						
105	0.27	0.25	0.23	0.21	0.21	0.20	0.16	0.16	0.17	0.18	0.18	0.21						
110	0.36	0.34	0.31	0.29	0.29	0.27	0.22	0.22	0.23	0.25	0.25	0.28						
115	0.48	0.45	0.42	0.39	0.38	0.37	0.30	0.31	0.32	0.33	0.35	0.39						
120	0.63	0.60	0.55	0.52	0.51	0.49	0.40	0.41	0.43	0.45	0.46	0.52						
125	0.82	0.78	0.73	0.69	0.67	0.65	0.54	0.55	0.58	0.60	0.62	0.68						
130	1.05	1.01	0.96	0.91	0.88	0.84	0.71	0.73	0.76	0.78	0.81	0.89						
135	1.31	1.28	1.23	1.17	1.13	1.08	0.92	0.95	0.98	1.01	1.05	1.13						
140	1.61	1.59	1.53	1.47	1.41	1.36	1.17	1.21	1.25	1.28	1.32	1.41						
145	1.93	1.91	1.86	1.79	1.73	1.67	1.47	1.50	1.54	1.57	1.63	1.73						
150	2.25	2.23	2.19	2.13	2.06	2.00	1.78	1.81	1.85	1.89	1.95	2.06						
155	2.56	2.55	2.50	2.45	2.38	2.33	2.11	2.14	2.18	2.22	2.28	2.38						
160	2.86	2.85	2.81	2.76	2.70	2.65	2.44	2.46	2.50	2.54	2.61	2.71						
165	3.14	3.13	3.09	3.04	2.99	2.95	2.77	2.78	2.82	2.87	2.93	3.02						
170	3.36	3.33	3.31	3.27	3.24	3.23	3.09	3.08	3.11	3.14	3.21	3.28						
175	3.47	3.46	3.44	3.43	3.42	3.44	3.34	3.33	3.35	3.36	3.41	3.46						
180	3.48	3.49	3.47	3.48	3.50	3.54	3.49	3.47	3.49	3.48	3.50	3.53						

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:02
Test Date:2019-08-21

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.405.8
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks: