

# LED Flood Light Series H



All product standard with **Philips Chip** and **Meanwell Driver**



# SPECIFICATION

## LED Flood Light H



### Features

- High luminous efficiency 120LM/W.
- Excellent heat dissipation support stable quality.
- Convention installation for linking in series.
- Long lifespan 50,000 hours.
- Energy saving up to 80%.
- 5 years warranty.

### Application

- Sport stadium
- Warehouse
- Airport

### Caution

- Please read the user manual before installation.
- Please install, connect and test the lamp according to local regulations, Lamps should always be installed or replaced with care by professional person.
- Ensure the power is switched off before installation.
- Please check whether the lamps are broken or not during shipping, broken items cannot be used anymore.
- Please keep the lamps and accessories away from kids to avoid hurt by mistakes.
- For protecting eyes, please do not watch the luminous surface for a long time,
- Do not cover anything on lamp and keep lamps away from fire or high temperature objects.
- Incorrect installation and using, keep the right to refuse after-sales service for those disassembled or repaired items.
- Switch the power off and cool down the lamp before cleaning.
- The lamp is only suitable for weak acid and weak base environment.
- Please DO NOT install this product in the following places:
  1. The place has a large quantity of lampblack and smoke, such as: kitchen and food processing factory etc.
  2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
  3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -20 and 50 degrees.

## PARAMETER

|                     |  |
|---------------------|--|
| Model No.           | LU-FLH-50W / LU-FLH-100W / LU-FLH-200W |
| Material            | AL Body and PC Cover                   |
| Size(mm)            | 50W:220*266*50    100W:296*346*60      |
|                     | 200W:360*398*60                        |
| Input Voltage       | AC110-277V                             |
| Power               | 50/100/200W                            |
| Driver              | Meanwell Driver                        |
| P.F.                | >0.9                                   |
| Luminous Flux       | 6000/12000/24000lm                     |
| Luminous Efficiency | 120lm/W                                |
| CRI                 | >70Ra                                  |
| Beam Angle          | 120                                    |
| IP Level            | IP65                                   |

- All product standard with **Philips Chip** and **Meanwell Driver**

