


LED IP44 Ceiling Light



5 years warranty



SPECIFICATION

LED IP44 Ceiling Light



Caution

- Please read the user manual before installation.
- Please install, connect and test the lamp according to local regulations, Lamps should always be installed or replaced with care by professional person.
- Ensure the power is switched off before installation.
- Please check whether the lamps are broken or not during shipping, broken items cannot be used anymore.
- Please keep the lamps and accessories away from kids to avoid hurt by mistakes.
- For protecting eyes, please do not watch the luminous surface for a long time,
- Do not cover anything on lamp and keep lamps away from fire or high temperature objects.
- Switch the power off and cool down the lamp before cleaning.
- The lamp is only suitable for weak acid and weak base environment.
- Please DO NOT install this product in the following places:
 1. The place has a large quantity of lampblack and smoke, such as: kitchen and food processing factory etc.
 2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
 3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -20 and 50 degrees.

Features


- Unique patent design, CE, ROHS listed .
- Low light decay, L70=50,000 Hours .
- High impact test .
- Long lifespan 50,000 hours.
- Energy saving up to 80%
- 5 years warranty.

Application

- Path
- Corridor
- Balcony

Dimension

Model No.	Size(mm)
LU-220C-44	220*48
LU-280C-44	280*48
LU-330C-44	330*48
LU-400C-44	400*48





PARAMETER

Model No.	LU-220C-44/LU-280C-44/LU-330C-44/LU-400C-44
Material	PC Body
Size(mm)	Ø220*48/Ø280*48/Ø330*48/Ø400*48
Input Voltage	AC220-240V
Power	15W/18W/24W/36W
Driver	IC Driver
P.F.	>0.9
Luminous Flux	1500lm/1800lm/2400lm/3600lm
Luminous Efficiency	100 lm/W
CRI	>80Ra
Beam Angle	120
IP Level	IP44

Package Details

Model	Carton(cm)	QTY/CTN	N.W./PCS(kg)	G.W./CTN(kg)
LU-220C-44	58*28*28	10	0.82	10
LU-280C-44	58*31*31	10	1.02	12
LU-330C-44	58*34*34	10	1.2	15

Light Source Test Report



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.